



How to control Wiper & Washer

Ways 1) Use of Hard Wire

(Terminal Cables in Housing = Input by Non-voltage Contact)



Ways 2) Use of PC or ASC Small Remocon



Optional Items

Pole Mount Adapter
A-BK6S(OW)



Front Direction 120 deg Pan Adjuster
A-PAN120




Replacement Capsule
A-RCP300C



Replacement Wiper Blade
A-RWB300



Replacement Capsule & Wiper Whole Unit
A-RCW300WU



4ch Compact Remote Controller
A-RM4CH



※Specifications are subject to change without prior notice

<http://www.kk-asc.com>

Manufactured by

ASC

ASC Corporation
3-16-9, Toranomom, Minato-ku, Tokyo 105-0001, Japan
Tel : +81-3-5473-7627 Fax : +81-3-5473-7628

(Wholesale for U.S.A Market only)
ASC-USA, INC.
5975 Shiloh Road, Suite 103, Alpharetta, GA 30005
Tel : 770-888-4674 / 1-888-988-4674 Fax : 770-888-4675

ASC Wiper Dome®

Housing A-ODW7-300 Series

For 1.0" CMOS Sensor Remote Cameras



FEATURES

We Customize Housing Spec to Meet Your Requirements !

Housing Material


Choice of Stainless SUS304 or Steel based on your budget.

Angle of Dome Capsule

In addition to Standard Slant 10 deg upward, horizontally 0 (Zero) deg to Slant 35 deg are available.

Peltier Cooling Device

Optional Peltier Active Cooling Device can maintain the temperature inside of housing not to exceed 40°C. Additional Cooling and Heating Unit is available for Extreme Hot/Cold Area.



Self-Cleaning *Optional Item

You can always keep Capsule Clean by using Self-Cleaning Function(POE Type Only). You can program Number of Wiper and Washer Control daily on minute basis for maximum 16 cameras. It goes a long way in Coastal Area or Snow Area.



Power Supply for Housing

You have a choice of POE, 12VDC and 24VAC. In case of POE, you need to wire one more ethernet cable for Camera.

Midspan for POE



AC Adapter for 12VDC



Washer Tank

Standard Size of Tank is 10L.(Approx. 700 times spray/Duration 1sec) Choice of Bax for tanks are Plastic, Steel and Stainless.

Photo: 10L Tank




Photo: Steel Box for 10L Tank
Nitto Model ORB-2044
Size 405(L) x 222(W) x 430(H)mm

Specifications

Operating Environment	Outdoor		
Operating Temperature	-20°C(-4F)-50°C(122F)		
	* Additional Cooling and Heating Unit will be installed for Extreme Hot/Cold Area.		
IP Rate	IP66		
Max Wind Load	60m sec(197ft/sec)		
Materials	Housing = Stainless (SUS304) or Steel Capsule: Acrylic(Clear = Light Loss 0)		
Color	Off-white (RAL9002 Similar) Powder Coat Finish		
Thermostat for Cooling/Heating	Peltier Cooling/Blower Cooling	ON 35°C(95F)	OFF 27°C(81F)
	Heater	ON 4.4°C(40F)	OFF 16°C((61F)
Standard Power Supply Unit for Housing (Cooling/Heating/Wiper/Washer)	90W Midspan Microchip Model PD-9601		
	AC Adapter 12VDC 80W Toki Trading Model SPU-105		
Weight	Model A-ODW7-300WA10S	Approx 22.6kg(50LBS) by Stainless 20.6kg(46LBS) by Steel	
	Peltier System: Add 1.5kg(3.3LBS) per Unit		
Compliance	RoHs, PSE, CE, RCM, UL(File# E313815)		

↳ Specifications are subject to change without prior notice for the improvement of products. -

How to Select Models




Capsule Slant Standard 10 degrees Model with Wiper

A-ODW7-300WA10S

(If No Peltier System, Bottom Basket Not Included)

Weight (Camera Not Included): Steel: 25.5kg (56.5LB)
Stainless Steel: 28kg(62LB)
Peltier System: Add 1.5kg(3.3LB) per Unit




Capsule Slant Standard 10 degrees Model with Wiper

A-ODW7-300WA35S

(If No Peltier System, Bottom Basket Not Included)

Weight (Camera Not Included): Steel: 26.8kg (59LB)
Stainless Steel: 30kg(66LB)
Peltier System: Add 1.5kg(3.3LB) per Unit



Capsule Slant Zero(0) Ceiling Mount

A-ODW7-300B

(If No Peltier System, Back Basket Not Included)

Weight (Camera Not Included): Steel: 18kg (40LB)
Stainless Steel: 20kg(44LB)
Peltier System: Add 1.5kg(3.3LB) per Unit

