


PowerDsine 9501GO

Single-port, Outdoor PoE Midspan, 60W, IEEE802.3at Compliant



PD-9501GO Specifications

No. of Ports	1
Pass Through Data Rates	10/100/1000 Mbps
Power over Ethernet Output	Pin Assignment and Polarity: 4/5 (+), 7/8 (-), 1/2(-), 3/6(+) Output Power Voltage: 55Vdc User Port Power: 60W guaranteed
Input Power Requirements	AC Input Voltage: 100 to 240 Vac AC Input Current: 2.0A @100-240 Vac AC Frequency: 50 to 60 Hz
Dimensions	214 mm x 150 mm x 70 mm 8.42 in. x 5.90 in. x 2.75 in
Weight	1.65 lbs (750g)
Indicators	No LED indicators
Connectors	Shielded rugged RJ-45 (with gasket)
Environmental Conditions	Operating Ambient Temperature: -40° to 122°F (-40 to 50°C) for 60W -40° to 131°F (-40 to 55°C) for 30W Operating Humidity: Maximum 95%, Non-condensing Storage Temperature: -40° to 185°F (-40° to 85°C) Storage Humidity: Maximum 95%, Non-condensing Operating Altitude: Up to 6,560 ft. (2000 m) Weather Rating: IP66, NEMA 4X
Reliability	MTBF: 150,000 hrs. @25°C
Thermal Rating	45 BTU/Hr (@240VAC)
Warranty	1-year
Regulatory Compliance	IEEE 802.3af (PoE, PoH Type1) IEEE 802.3at (PoE+ including 2-event, PoH Type 2), RoHS Compliant, WEEE Compliant, CE
Electromagnetic Emission & Immunity	FCC Part 15, Class B EN 55022 Class B EN 55024, EN61000-4-5 Class 5 (6kV CM) VCCI
Surge Protection	Meets Surge Protection as specified in GR-1089-CORE Issue 4 ITU-T K.20 6 kV on AC lines
Safety Approvals	UL60950-1 & UL60950-22 GS Mark
Other Standards and Approvals	Dust and water intrusion: EN60529, Level1P66; NEMA 250, Level 4X ASTM B-117 Corrosion Resistance

Overview

PowerDsine 9501GO Power over Ethernet (PoE) single-port Midspan offers a cost effective, IEEE 802.3at compliant solution for outdoor installations, guaranteeing 60 Watts of power and ensuring safe and reliable operation in outdoor environment of any standard PoE data terminal. It allows wireless LAN access points, security network cameras and other IP terminals to receive power, along with data, over standard Ethernet cables, leaving network infrastructure completely unaltered.



The 9501GO also offers surge protection for both the AC and the PoE ports ensuring the indoor equipment is protected from outdoor surges.

PD-9501GO Features

- Outdoor rated: IP66
- Extended temperature range -40°C , +55°C
- IEEE802.3at standard compliant
- Power provided using all 4 pairs
- Supports 10/100/1000Mbps data rates
- Plug 'n Play installation (installer does not have to open unit)
- Supports both 802.3af and 802.3at Powered devices
- Includes integral surge protection

PD-9501GO Midspan

PD-9501GO with outdoor mounting bracket



Ordering Information

Part Number	Name	Description
PD-9501GO/AC-NA	PowerDsine 9501GO	1-port, 60W 802.3at Gigabit PoE outdoor midspan with North American power connector
PD-9501GO/AC-INTL	PowerDsine 9501GO	1-port, 60W 802.3at Gigabit PoE outdoor midspan with international power cord
PD-OUT/MBK	PowerDsine OUT MBK	Mounting brackets for outdoor unit

For More Information

North America
PowerDsineUSA@microsemi.com

EMEA
(Europe, Middle East, Africa)
PowerDsine@microsemi.com

LATAM
(Latin America)
PowerDsineLATAM@microsemi.com

APAC
(Asia Pacific)
PowerDsineAPAC@microsemi.com



Microsemi

Power Matters.

Microsemi Corporation (NASDAQ:MSCC) offers the industry's most comprehensive portfolio of semiconductor and networking technology. PowerDsine® PoE Systems, a Microsemi brand, is the thought leader in energy efficient, high power PoE technology. Learn more at microsemi.com/powerdsine

©2011 Microsemi Corporation. All rights reserved. Microsemi and the Microsemi logo are trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners.

MSC-PD-DS-9501GO-1.2012