



### Indoor & Under Canopy Dome Housing

**A-SWD5**

6 digits registered model name(UL & PSE)    After 7 digits shows optional specifications

**Capsule**  
C = Clear  
T = Tinted

BH2 = Type 24VAC Blower and heater installed  
BH12 = Type 12VDC Blower and heater installed  
BH12(POE) = Type 12VDC Blower, heater and PoE Splitter installed in housing \*1, \*2  
BH12(POE+M) = Type 12VDC Blower, heater and PoE Splitter installed in housing and Midspan are packed in product box. \*1, \*2

**Housing Color**  
Nothing = Standard (Off-White)  
(SV) = Silver

### Specifications

Operating Environment	Indoor or Under Canopy
Operating Temperature	-60°C(-76°F)~+45°C(113°F) (AC24V/DC12V 25W•POE 60W) Note: It is subject to the specification of camera.
IP Rate	IP54 (Vent Holes "Open") IP66 (Vent Holes "Closed" with provided Rubber)
Housing	Material = PC/ABS UL94 V-0    Standard Color = Off-White (RAL9002 Similar)    Powder Coat Finish Optional Color : (SV) = Silver *Vandal Resistant M4 Screws x 7 pcs. & Tool Set Model A-VSM4TL is optional.
Capsule	Material = PC UL94 V-0 Light Loss : [C] = Clear = Almost zero [T] = Tinted = Approx. 60%
Weight	Approx. 1.2kgs (2.7 lbs)    (1.5kgs (3.3lbs) with Blower and Heater)
Heater (Optional)	[BH 2] = 24VAC 25W [BH12] = 12VDC Input 25W Standard (Optional 6W/12W) [BH12 (POE)] [BH12 (POE+M)] = 12VDC Input 12W Standard (Optional 6W/25W) Auto by thermostat 4.4°C (40°F) = ON    16°C (60°F) = OFF
Blower (Optional)	[BH 2] = 24VAC Input [BH12] = 12VDC Input [BH12 (POE)] [BH12 (POE+M)] = 12VDC Input Manufacturer: Nidec Servo Corp. EUDC12D8 DC12V 0.04A 0.5W    DC12V 0.04A 0.5W Auto by thermostat 35°C (95°F) = ON    27°C (80°F) = OFF
Input Terminal (Provided)	Sato Parts ML-4000-AP-2PGY (Acceptable Cable AWG16-26)
Recommended Screw	M4 Screw x 4 (Not included in product)
Standard & Compliance	RoHS, UL (File #E313815), CE, EAC, RCM

\*1 Due to size and specification of camera splitter may not be installed in housing.  
\*2 As regards the specification of both Splitter and Midspan, you are requested to obtain our confirmation in advance before ordering.